

NETWORK ÜRÜNLER			
ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>2MP IP KAMERA</b>			
<b>YENİ</b>			
<b>DS-2CD1021G2-LIUF</b> (Dahili mikrofon)		<b>2 MP Smart Hybrid Light Bullet Network Kamera</b> 1/2.9" Progressive Scan CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included. Motion Detection 2.0	<b>84</b>
<b>YENİ</b>			
<b>DS-2CD1121G2-LIUF</b> (Dahili mikrofon)		<b>2 MP Smart Hybrid Light Dome Network Kamera</b> 1/2.9" Progressive Scan CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included. Motion Detection 2.0	<b>84</b>
<b>DS-2CD1023G2-LIUF</b> (Dahili mikrofon)		<b>2 MP Smart Hybrid Light Bullet Network Kamera</b> High quality imaging with 2 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Water and dust resistant (IP67);Motion Detection 2.0	<b>91</b>
<b>DS-2CD1323G2-LIUF</b> (Dahili mikrofon)		<b>2 MP Smart Hybrid Light Turret Network Kamera</b> High quality imaging with 2 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);	<b>91</b>
<b>DS-2CD1023G2-LIUF/M</b> (Dahili mikrofon)		<b>2 MP Smart Hybrid Light Bullet Network Kamera</b> <b>Full Metal</b> High quality imaging with 2 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Water and dust resistant (IP67);Motion Detection 2.0	<b>99</b>
<b>YENİ</b>			
<b>DS-2CD1T23G2-LIUF/SL</b> (Dahili mikrofon)	 	<b>2 MP Smart Hybrid Light Bullet Network Kamera</b> <b>Live Guard</b> 1/3" Progressive CMOS, ICR,1920 x 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: <b>up to 50m</b> , Built-in microphone & speaker, audio & strobe light alarm, DC12V & PoE, Support mobile monitoring via Hik-Connect; Support on-board storage up to 512 GB (SD card slot) - Motion Detection 2.0	<b>131</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD1027G2H-LIUF (Dahili mikrofon)	 ColorVu	2 MP ColorVu & Smart Hybrid Light Bullet Network Kamera High quality imaging with 2 MP resolution; Support Human and Vehicle Detection Motion Detection 2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Built-in microphone for real-time audio security; Water and dust resistant (IP67); Motion Detection 2.0	117
DS-2CD1327G2H-LIUF (Dahili mikrofon)	 ColorVu	2 MP ColorVu & Smart Hybrid Light Dome Network Kamera High quality imaging with 2 MP resolution; Support Human and Vehicle Detection Motion Detection 2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Built-in microphone for real-time audio security; Water and dust resistant (IP67); Motion Detection 2.0	117
<b>YENİ</b>			
DS-2CD1T27G2H-LIUF/SL (Dahili mikrofon)	 ColorVu	<b>2 MP ColorVu &amp; Smart Hybrid Light Bullet Network Kamera Live Guard</b> 1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included; Motion Detection 2.0	150
DS-2CD1623G2-LIZSU (Dahili mikrofon)		<b>2MP Motorize Varifokal Lensli IR Bullet Kamera Smart Hybrid Light &amp; Motion Detection 2.0</b> 1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio *power supply is not included	190
DS-2CD1723G2-LIZSU (Dahili mikrofon)		<b>2MP Motorize Varifokal Lensli IR Dome Kamera Smart Hybrid Light &amp; Motion Detection 2.0</b> 1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect;*-S: alarm and audio *power supply is not included	190
DS-2CD2523G2-LIS2U (Dahili mikrofon)	 AcuSense	<b>2MP IR Mini Dome Acusense Kamera Acusense &amp; Smart Hybrid Light &amp; 120dB WDR</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;*-S model: Audio/Alarm IO * -2U:Built-in Dual-Array Microphone	239

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<p><b>YENİ</b></p> <p><b>DS-2CD2T23G2-LIS2U/SL</b></p> <p></p>	 	<p><b>2MP Bullet Acusense Kamera &amp; Live Guard &amp; Acusense &amp; Smart Hybrid Light &amp; 120dB WDR</b></p> <p>1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m *-2U:Built-in Dual-Array Microphone;</p>	236
<b>4MP IP KAMERA</b>			
<p><b>YENİ</b></p> <p><b>DS-2CD1041G2-LIUF</b> (Dahili mikrofon)</p>		<p><b>4 MP Smart Hybrid Light Fixed Bullet Network Kamera</b></p> <p>1/2.8" Progressive Scan CMOS, ICR, 2560 x 1440:25fps(P)/30fps(N), H.265+/H.264+&amp;H.264, 3D DNR, BLC, IR range: up to 20m, DC12V &amp; PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included;Motion Detection 2.0</p>	117
<p><b>YENİ</b></p> <p><b>DS-2CD1141G2-LIUF</b> (Dahili mikrofon)</p>		<p><b>4 MP Smart Hybrid Light Fixed Dome Network Kamera</b></p> <p>1/2.8" Progressive Scan CMOS, ICR, 2560 x 1440:25fps(P)/30fps(N), H.265+/H.264+&amp;H.264, 3D DNR, BLC, IR range: up to 20m, DC12V &amp; PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included;Motion Detection 2.0</p>	117
<p><b>DS-2CD1043G2-LIUF</b> (Dahili mikrofon)</p>		<p><b>4MP Smart Hybrid Light Bullet Network Kamera</b></p> <p>High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0</p>	128
<p><b>DS-2CD1343G2-LIUF</b> (Dahili mikrofon)</p>		<p><b>4MP Smart Hybrid Light Turret Network Kamera</b></p> <p>High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0</p>	128
<p><b>DS-2CD1043G2-LIUF/M</b> (Dahili mikrofon)</p>		<p><b>4MP Smart Hybrid Light Bullet nETWORK Kamera Full Metal</b></p> <p>High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0</p>	135

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
<b>DS-2CD1T43G2-LIUF/SL</b> (Dahili mikrofon)		<b>4MP Smart Hybrid Light Bullet Network Kamera Live guard</b> 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, Smart Hybrid Light with IR and white light, range: up to 50m, DC12V & PoE, Motion 2.0 human and vehicle classification, Support mobile monitoring via Hik-Connect; *power supply not included *-F: Built-in Microphone, TF card slot; Motion Detection 2.0	<b>168</b>
<b>DS-2CD1047G2H-LIUF</b> (Dahili mikrofon)		<b>4MP ColorVu &amp; Smart Hybrid Light Bullet Network Kamera</b> 1/3" Progressive CMOS, ICR, 2560 x 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included; Motion Detection 2.0	<b>157</b>
<b>DS-2CD1347G2H-LIUF</b> (Dahili mikrofon)		<b>4MP ColorVu &amp; Smart Hybrid Light Turret Network Kamera</b> 1/3" Progressive CMOS, ICR, 2560 x 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included; Motion Detection 2.0	<b>157</b>
<b>YENİ</b>			
<b>DS-2CD1T47G2H-LIUF/SL</b> (Dahili mikrofon)		<b>4MP ColorVu &amp; Smart Hybrid Light Bullet Network Kamera</b> 1/3" Progressive CMOS, ICR, 2560 x 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; <b>IR and white light, up to 50m</b> *-F: SD Card Slot (up to 512GB) *power supply is not included; Motion Detection 2.0	<b>212</b>
<b>DS-2CD1643G2-LIZSU</b> (Dahili mikrofon)		<b>4MP Smart Hybrid Light Motorize Varifokal Lensli Bullet Kamera 120dB WDR</b> 1/3" Progressive CMOS, ICR, 2560 x 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect; *-S: alarm and audio; *power supply is not included ; Motion Detection 2.0	<b>219</b>
<b>DS-2CD1743G2-LIZSU</b> (Dahili mikrofon)		<b>4MP Smart Hybrid Light Motorize Varifokal Lensli Dome Kamera 120dB WDR</b> 1/3" Progressive CMOS, ICR, 2560 x 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect; *-S: alarm and audio; *power supply is not included	<b>219</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>DS-2CD2043G2-LI2U</b> (Dahili mikrofon)  		<b>4M Smart Hybrit Light Bullet Network Kamera Acusens &amp; Full-Metal &amp; VCA &amp; 120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED;EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;* -2U:Built-in Dual-Array Microphone	228
<b>DS-2CD2143G2-LIS2U</b> (Dahili mikrofon)  		<b>4M Smart Hybrit Light Dome Network Kamera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED;EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;* -S model: Audio/Alarm IO * -2U:Built-in Dual-Array Microphone	239
<b>DS-2CD2543G2-LIS2U</b> (Dahili mikrofon)  		<b>4M Smart Hybrit Light Dome Network Kamera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;* -S model: Audio/Alarm IO * -2U:Built-in Dual-Array Microphone	262
<b>YENİ</b>		<b>4M Smart Hybrit Light Bullet Network Kamera Acusens &amp; Full Meal &amp; VCA &amp;120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m * -2U:Built-in Dual-Array Microphone	251
<b>YENİ</b>		<b>4M Darkfight Bullet Network Kamera Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 x 1520, 1920 x 1080, 1280 x 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone;-/SL: live-guard	266

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD2146G2H-ISU (Powered by Darkfighter)		<b>4M Darkfight Dome Network Kamera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 x 1520, 1920 x 1080, 1280 x 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 30 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	266
<b>YENİ</b> DS-2CD2T46G2H-IS2U/SL (Powered by Darkfighter)  AcuSense	 	<b>4M Darkfight Bullet Network Kamera Live Gaurd Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 x 1520, 1920 x 1080, 1280 x 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance	296
<b>YENİ</b> DS-2CD2047G3-LI2UY/SL (Darkfighter)  ColorVu 3.0	 	<b>4M ColorVu + Smart Hybrid Bullet Network Kamera Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/30fps(2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK- Connect cloud service; -U:Built-in micphone	357
<b>YENİ</b> DS-2CD2347G3-LIS2UY/SL (Darkfighter)  ColorVu 3.0	 	<b>4M ColorVu + Smart Hybrid Turret Network Kamera Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/30fps(2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 30m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK- Connect cloud service; -U:Built-in micphone	357
<b>YENİ</b> DS-2CD2T47G3-LIS2UY/SL (Darkfighter)  ColorVu 3.0	 	<b>4M ColorVu + Smart Hybrid Bullet Network Kamera Live Gaurd &amp; Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/30fps(2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK- Connect cloud service;	418

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>DS-2CD2643G2-LIZS2U</b> (Dahili mikrofon)  		<b>4MP Motorize Varifokal Lensli Smart Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 60m; Audio/Alarm IO; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone	399
<b>DS-2CD2743G2-LIZS2U</b> (Dahili mikrofon)  		<b>4MP Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m *-2U:Built-in Dual-Array Microphone	399
<b>DS-2CD2646G2HT-IZS(2.8-12mm)</b> (Powered by Darkfighter)  		<b>4MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) Acusens &amp; Full Metal &amp; VCA120dB WDR</b> 1/3" Progressive Scan CMOS((C) model); H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.003 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520,1920x1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm I/O *non-(C) model:1/2.7" Progressive Scan CMOS	475
<b>YENİ</b>  <b>DS-2CD2746G2H-IPTRZS(2.8-12mm)</b> (Powered by Darkfighter)  		<b>4MP PTRZ Motorize Varifokal Lensli IR Dome Kamera (H.265+) Acusens &amp; Full Metal &amp; VCA120dB WDR &amp; PTRZ</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 x 1520, 1920 x 1080, 1280 x 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	475
<b>YENİ</b>  <b>DS-2CD2647G3-LIZS2UY/SL</b> (Darkfighter)  	  	<b>4MP ColorVu Motorize Varifokal Lensli Hybrid Light Bullet Kamera (H.265+) Acusens &amp; Full Metal &amp; VCA120dB WDR</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008Lux @ (F1.2, AGC ON),0 Lux with light 25fps/30fps(2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; /:SL Live Guard	657

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
DS-2CD2747G3T-LIZSY(2.8-12mm) (Darkfighter)  ColorVu 3.0		<b>4MP Motorize Varifokal Lensli Smart Hybrid Light Dome Kamera Acusens &amp; Full Metal &amp; VCA 120dB WDR</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;	657
<b>6MP IP KAMERA</b>			
DS-2CD1063G2-LIUF (Dahili mikrofon)		<b>6MP Mini IR Bullet Kamera Smart Hybrid Light</b> High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional); Motion detection 2.0	164
DS-2CD1363G2-LIUF (Dahili mikrofon)		<b>6MP Turret Kamera Smart Hybrid Light &amp; Motion Detection 2.0</b> High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional);	164
<b>YENİ</b>			
DS-2CD1T63G2-LIUF/SL (Dahili mikrofon)	 	<b>6MP Bullet Kamera Smart Hybrid Light &amp; Motion Detection 2.0 &amp; Live Guard</b> 1/3" Progressive CMOS, ICR,3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone & speaker, audio & strobe light alarm, DC12V & PoE, Support mobile monitoring via Hik-Connect; *power supply is not included	186
DS-2CD1067G2H-LIUF (Dahili mikrofon)  ColorVu		<b>6MP Mini Bullet Kamera (H.265+) ColorVu &amp; Smart Hybrid Light &amp; Motion Detection 2.0</b> 1/3" Progressive CMOS, ICR,3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included	183
DS-2CD1367G2H-LIUF (Dahili mikrofon)  ColorVu		<b>6MP Mini Bullet Kamera ColorVu &amp; Smart Hybrid Light &amp; Motion Detection 2.0</b> 1/3" Progressive CMOS, ICR,3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included	183

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
<b>DS-2CD1T67G2H-LIUF/SL</b> (Dahili mikrofon)  		<b>6MP Mini Bullet Kamera (H.265+) ColorVu &amp; Smart Hybrid Light &amp; Motion Detection 2.0 &amp; Live Guard</b> 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; 50 m IR *-F: SD Card Slot (up to 512GB) *power supply is not included /SL: live Guard	<b>230</b>
<b>DS-2CD1663G2-LIZSU</b> (Dahili mikrofon)		<b>6MP Smart Hybrit Light Motorize Varifokal Lensli Bullet Kamera (H.265+) 120dB WDR</b> 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio *power supply is not included	<b>230</b>
<b>DS-2CD1763G2-LIZSU</b> (Dahili mikrofon)		<b>6MP Smart Hybrit Light Motorize Varifokal Lensli Dome Kamera (H.265+) 120dB WDR</b> 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio *power supply is not included	<b>230</b>
<b>8MP IP KAMERA</b>			
<b>DS-2CD2083G2-LI2U</b> (Dahili mikrofon)  		<b>8M Smart Hybrit Light Mini Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp; 120DB WDR</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; * -2U: Built-in Dual-Array Microphone	<b>285</b>
<b>DS-2CD2183G2-LIS2U</b> (Dahili mikrofon)  		<b>8M Smart Hybrit Light Dome Camera Acusens &amp; Full Metal &amp; VCA &amp; 120DB WDR</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO * -2U: Built-in Dual-Array Microphone	<b>296</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>DS-2CD2583G2-LI2U</b> (Dahili mikrofon)  		<b>8M Smart Hybrit Light Mini Dome Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO *-2U:Built-in Dual-Array Microphone	323
<b>YENİ</b>  <b>DS-2CD2T83G2-LIS2U/SL</b> ( Dahili mikrofon)  	  	<b>8M Smart Hybrit Light Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; live guard</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x18:00, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m *-2U:Built-in Dual-Array Microphone	323
<b>YENİ</b>  <b>DS-2CD2086G2H-I2U/SL</b> ( Darkfighter)  	  	<b>8M Darkfight mini Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/24fps(3840x2160);25fps/30 fps (3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720) VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	342
<b>DS-2CD2186G2H-ISU</b> (Darkfighter)  		<b>8M Darkfight Dome Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/24fps(3840x2160);25fps/30 fps (3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720) VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 30 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	357
<b>YENİ</b>  <b>DS-2CD2T86G2H-IS2U/SL</b> ( Darkfighter)  	  	<b>8M Darkfight Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b> 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/24fps(3840x2160);25fps/30 fps (3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance	429

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<p><b>YENİ</b></p> <p><b>DS-2CD2087G3-LI2UY/SL</b> (Darkfighter)</p> <p><b>ColorVu 3.0</b></p>	 	<p><b>8M ColorVu+ Hybrid mini Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b></p> <p>1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/24fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone</p>	418
<p><b>YENİ</b></p> <p><b>DS-2CD2387G3-LIS2UY/SL</b> (Darkfighter)</p> <p><b>ColorVu 3.0</b></p>	 	<p><b>8M ColorVu+ Hybrid Dome Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b></p> <p>1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/24fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 30m DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone</p>	426
<p><b>YENİ</b></p> <p><b>DS-2CD2T87G3-LIS2UY/SL</b> (Darkfighter)</p> <p><b>ColorVu 3.0</b></p>	 	<p><b>8M ColorVu+ Hybrid Bullet Camera Acusens &amp; Full Metal &amp; VCA &amp;120DB WDR &amp; Live Guard</b></p> <p>1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/24fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;</p>	494
<p><b>DS-2CD2683G2-LIZS2U</b> (Power By Darkfighter)</p> <p><b>AcuSense</b></p>		<p><b>8MP Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b></p> <p>1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 60m; DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone</p>	498
<p><b>DS-2CD2783G2-LIZS2U</b> (Power By Darkfighter)</p> <p><b>AcuSense</b></p>		<p><b>8MP Motorize Varifokal Lensli Hybrid Light Dome Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b></p> <p>1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m; DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone</p>	498

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<p><b>YENİ</b></p> <p><b>DS-2CD2686G2HT-IZS2U/SL</b> (Darkfighter)</p> <p></p>	 	<p><b>8MP Motorize Varifokal Lensli IR Bullet Kamera Acusens &amp; Full Metal &amp; VCA120dB WDR &amp; Live Guard</b></p> <p>1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *Junction box is included in the camera package</p>	646
<p><b>YENİ</b></p> <p><b>DS-2CD2786G2H-IPTRZS</b> (Darkfighter)</p> <p></p>	 	<p><b>8MP Motorize Varifokal Lensli IR Dome Kamera Acusens &amp; Full Metal &amp; VCA120dB WDR &amp; PTRZ</b></p> <p>1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *Junction box is included in the camera package</p>	566
<p><b>YENİ</b></p> <p><b>DS-2CD2687G3-LIZS2UY/SL</b> (Darkfighter)</p> <p></p>	 	<p><b>8MP Colorvu Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR &amp; Live Guard</b></p> <p>1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;</p>	752
<p><b>YENİ</b></p> <p><b>DS-2CD2787G3T-LIZSY</b> (Darkfighter)</p> <p></p>	 	<p><b>8MP Colorvu Motorize Varifokal Lensli Hybrid Light Dome Kamera Acusens &amp; Full Metal &amp; VCA&amp;120dB WDR</b></p> <p>1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;</p>	752
<b>Panoramic &amp; Live Guard Cameras</b>			
<p><b>YENİ</b></p> <p><b>DS-2CD2T46G2P-LSU/SL</b></p> <p></p>	 	<p><b>2*4MP Panoramic &amp; Live Guard Cameras Strobe light &amp; Audio</b></p> <p>2*1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.003 lux @(F1.6, AGC ON), 0 lux with IR; 20fps(3632x1632),VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&amp;PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in microphone and speaker, Audio/Alarm I/O; 180° FOV</p>	277

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
DS-2CD2T47G2P-LSU/SL 		<b>2 4MP ColorVu Panoramic &amp; Live Guard Cameras</b> <b>2*1/1.8" Progressive Scan CMOS; Strobe light &amp; Audio</b> H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on; 20fps(5120x1440),VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in microphone and speaker, Audio/Alarm I/O;180° FOV	369
<b>YENİ</b>			
DS-2CD2T87G2P-LSU/SL 		<b>2 8MP ColorVu Panoramic &amp; Live Guard Cameras</b> <b>Strobe light &amp; Audio</b> 2*1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on; 20fps(5120x1440),VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in microphone and speaker, Audio/Alarm I/O; 180° FOV	448
<b>Balıkgözü KAMERA</b>			
DS-2CD2955G0-ISU 		<b>5MP Balıkgözü KAMERA</b> 1/2.9" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.016 lux@(F2.2, AGC ON), 0 lux with IR; 25fps/30fps(2560x1920, 2048x1536, 1920x1080); F2.2, field of view: 180°(H)x180°(V); 120dB WDR; 2 streams; 3D DNR; BLC; ICR; EXIR, up to 8m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service build-in-mic	334
<b>HeatPro Termal KAMERA</b>			
DS-2TD2617-6/QA 		<b>4MP optical Bullet Thermal Kamera</b> 160 × 120 resolution, 17 μm, VOx UFPA, NETD < 40 mK (25 °C, F# = 1.1) High accuracy temperature exception alarm, -20 °C to 150 °C (-4 °F to 302 °F), ± 8 °C (±14.4 °F) Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR Support smoking detection algorithm Support sun-reflection filter;Focal Length 6.2 mm	836
DS-2TD2617-3/QA 		<b>4MP optical Bullet Thermal Kamera</b> 160 × 120 resolution, 17 μm, VOx UFPA, NETD < 40 mK (25 °C, F# = 1.1) High accuracy temperature exception alarm, -20 °C to 150 °C (-4 °F to 302 °F), ± 8 °C (±14.4 °F) Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR Support smoking detection algorithm Support sun-reflection filter;Focal Length 3.1 mm	794
DS-2TD2628-3/QA 		<b>4MP optical Bullet Thermal Kamera</b> 256 × 192 resolution, 12 μm, VOx UFPA, NETD < 40 mK (25°C, F1.0) Video content analysis: vehicle/human classification Temperature exception alarm for fire prevention, -20°C to 150°C (- 4°F to 302°F), ± 8°C (± 14.4°F) Support smoking detection algorithm Support sun-reflection filter algorithm Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR	988

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>PTZ KAMERALAR</b>			
<b>IP PTZ KAMERA</b>			
<b>DS-2DE2C400MWG-E</b>		<p><b>4 MP Network IR 2-inch PT Dome (H.265+, 30m IR)</b>            1/2.7" Progressive Scan CMOS            Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR            2.8 mm, horizontal FOV 94°, vertical FOV 49°, diagonal FOV 114°            4 mm, horizontal FOV 70°, vertical FOV 35°, diagonal FOV 85°            White Light Distance: up to 30 m IR Distance: up to 30 m            Digital WDR, BLC, HLC, 3D DNR, Built-in Microphone, Built-in Speaker, audible warning when alarm triggers, POE</p>	<b>152</b>
<b>DS-2DE2C400SCG-E</b>		<p><b>4 MP Network ColorVu 2-inch live guard PT Dome (H.265+, 30m IR)</b>            1/2.8" Progressive Scan CMOS 2560 x 1440            Color: 0.001 Lux @(F1.0, AGC ON), B/W: 0 Lux with IR            2.8 mm, horizontal FOV 105.7°, vertical FOV 57.3°, diagonal FOV 124.9°            4 mm, horizontal FOV 88.7°, vertical FOV 44.7°, diagonal FOV 107.5°            White Light Distance: up to 30 m            Digital WDR, BLC, HLC, 3D DNR, Built-in Microphone, Built-in Speaker</p>	<b>239</b>
<b>DS-2SE2C400MWG-E/14</b>		<p><b>4MP Dual-lens, 2 inch live guard PT Dome , 30m IR)</b></p> <ul style="list-style-type: none"> <li>· Capture a large area and details at the same time</li> <li>· Support Human and Vehicle detection</li> <li>· Smart Hybrid Light: advanced technology with long range</li> <li>· Hik-Connect cloud service and app for remote management and views of devices</li> <li>· Built-in microphone and speaker for real-time audio security</li> <li>· Built-in memory card slot, support microSD/SDHC/SDXC card, up to 512 GB</li> <li>· Water and dust resistant (IP66)</li> </ul>	<b>239</b>
<b>DS-2DE4215IW-DE</b>		<p><b>2MP Network Dış Ortam IR PTZ Kamera, Deep learning</b>            1/2.8" progressive scan CMOS High quality imaging with 2 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 15x optical zoom and 16x digital zoom provide close up views over expansive areas. WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus            Expansive night view with up to 100 m IR distance            Support H.265+/H.265 video compression</p>	<b>623</b>
<b>DS-2DE4425IW-DE</b>		<p><b>4MP Network Dış Ortam IR PTZ Kamera</b>            1/2.8" progressive scan CMOS. High quality imaging with 4 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 25x optical zoom and 16x digital zoom provide close up views over expansive areas            WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus            Expansive night view with up to 100 m IR distance            Support H.265+/H.265 video compression</p>	<b>756</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2SE4C425MWG-E/RB/14  ColorVu AcuSense		<p><b>4MP Bullet lens:4MP, 30m White Light PTZ lens</b></p> <ul style="list-style-type: none"> <li>Captures a large area and great details at the same time</li> <li>High quality imaging with 4 MP resolution</li> <li>Focuses on human and vehicle targets classification based on deep learning</li> <li>Excellent low-light performance with powered-by-DarkFighter technology and ColorVu technology</li> <li>Secures an expansive area with 25 x optical zoom and 16 x digital zoom</li> <li>Expansive night view with up to 100 m IR distance &amp; 30 m white light</li> <li>Build-in speaker and dual-microphone for real-time high quality audio security</li> <li>Active strobe light and audio alarm to warn intruders off</li> <li>Supports 12 VDC &amp; PoE+</li> </ul>	859
DS-2SE4C425MWG-E/26(F0)  ColorVu AcuSense		<p><b>4MP Network Dış Ortam IR PTZ Kamera</b></p> <ul style="list-style-type: none"> <li>Captures a large area and great details at the same time</li> <li>High quality imaging with 4 MP resolution</li> <li>Excellent low-light performance with powered-by-DarkFighter technology</li> <li>Secures an expansive area with 25x optical zoom and 16x digital zoom</li> <li>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus, rapid focus</li> <li>Expansive night view with up to 200 m IR distance</li> <li>Supports 24 VAC &amp; Hi-PoE</li> <li>Active strobe light and audio alarm to warn intruders off</li> </ul>	946
DS-2DE7A432MWG-EB  AcuSense		<p><b>4MP Network Dış Ortam IR PTZ Kamera, Deep learning</b></p> <ul style="list-style-type: none"> <li>1/1.8" progressive scan CMOS</li> <li>Up to 2560 x 1440@30fps resolution</li> <li>Min. illumination:</li> <li>Color: 0.0005 Lux @(F1.2, AGC ON)</li> <li>B/W: 0.0001 Lux @(F1.2, AGC ON)</li> <li>0 Lux with IR</li> <li>32x optical zoom, 16x digital zoom</li> <li>WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus</li> <li>White light: up to 100 m / IR: up to 150 m</li> <li>24 VAC &amp; Hi-PoE</li> <li>Support H.265+/H.265 video compression</li> <li>Support audio visual alarm</li> </ul>	1410
YENİ  DS-2SE7C432MWG-EB  ColorVu AcuSense		<p><b>4MP Network Dış Ortam IR PTZ Kamera ( 32X, 200m IR, IP66, deep learning)</b></p> <ul style="list-style-type: none"> <li>Captures a large area and great details at the same time</li> <li>High quality imaging with 4 MP resolution</li> <li>Excellent low-light performance with powered-by-DarkFighter technology</li> <li>Secures an expansive area with 32x optical zoom and 16x digital zoom</li> <li>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus, rapid focus</li> <li>Expansive night view with up to 200 m IR distance</li> <li>Supports 24 VAC &amp; Hi-PoE</li> <li>Active strobe light and audio alarm to warn intruders off</li> </ul>	1524

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>WIFI Camera</b>			
<b>YENİ</b>			
<b>DS-2CV2021G2-IDW</b>		<b>2MP Wi-Fi Bullet Camera</b> 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080/1280x720: 25fps(P)/30fps(N), 2.8/4mm lens, H.265+/H.265/H.264+/H.264/MJPEG, dual-stream, 3D DNR,support on-board storage up to 256GB(SD card slot), Build-in microphone and speaker, Build-in external Dual-Antenna 2.4GHz Wi-Fi, 802.11b/g/n. *power supply included;*SD Card not included *(W) version models support mobile monitoring via Hik-Connect	<b>91</b>
<b>YENİ</b>			
<b>DS-2CV2041G2-IDW</b>		<b>4MP Wi-Fi Bullet Camera</b> 1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1440:30fps, 2304x1296/1920x1080/1280x720: 25fps(P)/30fps(N), H.265+/H.264+/H.264/MJPEG, Dual-stream, WDR, 3D DNR, support on-board storage up to 256GB(SD card slot), Build-in microphone and speaker, Build-in external Dual-Antenna 2.4GHz Wi-Fi, 802.11b/g/n.*power supply included *SD Card not included *(W) version models support mobile monitoring via Hik-Connect	<b>128</b>
<b>YENİ</b>			
<b>DS-2CV2Q21G1-IDW</b>		<b>2MP Wi-Fi Indoor PT camera</b> 1/2.8" Progressive CMOS, ICR,1920x1080: 25fps(P)/30fps(N), H.265+/H.265,3D DNR, support on-board storage up to 256GB, Build-in microphone and speaker, two-way talk, support two-way audio, Support mobile monitoring via Hik-Connect 5VDC power supply is included.	<b>84</b>
<b>YENİ</b>			
<b>DS-2DE2C200IWG/W</b>		<b>2MP Wi-Fi outdoor PT camera</b> 1/2.7" Progressive Scan CMOS Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR 2.8 mm, horizontal FOV 105°, vertical FOV 58°, diagonal FOV 123° 4 mm, horizontal FOV 81°, vertical FOV 44°, diagonal FOV 97° IR Distance: up to 30 m Digital WDR, BLC, HLC, 3D DNR,Built-in Microphone,Built-in Speaker,audible warning when alarm triggers;Wi-Fi Connection	<b>124</b>
<b>YENİ</b>			
<b>DS-2DE2C400IWG/W</b>		<b>4MP Wi-Fi outdoor PT camera</b> 1/2.7" Progressive Scan CMOS Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR 2.8 mm, horizontal FOV 94°, vertical FOV 49°, diagonal FOV 114° 4 mm, horizontal FOV 70°, vertical FOV 35°, diagonal FOV 85° IR Distance: up to 30 m Digital WDR, BLC, HLC, 3D DNR,Built-in Microphone,Built-in Speaker,audible warning when alarm triggers;Wi-Fi Connection	<b>161</b>
<b>YENİ</b>			
<b>DS-2CD2423G2-IW</b>		<b>2MP Wi-Fi Cube Camera</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color:0 lux with IR; 25Fps/30fps(1920x1080); 2 streams; DWDR; 3D DNR; ICR; EXIR, up to 10m; support AI human body detection; support on- board storage up to 512GB(SD card slot), Hik-Connect cloud service, Build-in microphone and speaker; Built-in 2.4G Wi-Fi, 802.11b/g/n; 12VDC & PoE power supply. *SD card is not included. *Power supplier is not included	<b>84</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
<b>DS-2CD2443G2-IW</b>		<b>4MP Wi-Fi Cube Camera</b> 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0 lux with IR; 20Fps0(2560x1440); 2 streams; DWDR; 3D DNR; ICR; EXIR, up to 10m; support AI human body detection; support on-board storage up to 512GB(SD card slot), Hik-Connect cloud service, Build-in microphone and speaker; Built-in 2.4G Wi-Fi, 802.11b/g/n; 12VDC & PoE power supply. *SD card is not included. *Power supplier is not included	<b>113</b>
<b>Solar Kamera</b>			
<b>DS-2DE2C200IWG-K/4G/C05S10</b>		<b>2MP 4G Solar PT Camera</b> 2MP,1920x1080,4G Connection 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Built-in mic & speaker for two-way audio Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m Built-in 8 GB eMMC storage ; IP66 for protection against dust and water Solar panel: 10 W, battery: 50 Wh 36-hour continuous power supply in proactive mode on cloudy or rainy days	<b>388</b>
<b>DS-2DE2C400IWG-K/4G/C05S10</b>		<b>4MP 4G Solar PT Camera</b> 4MP,2560x1440,4G Connection 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Built-in mic & speaker for two-way audio Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m Built-in 8 GB eMMC storage ; IP66 for protection against dust and water Solar panel: 10 W, battery: 50 Wh 36-hour continuous power supply in proactive mode on cloudy or rainy days	<b>429</b>
<b>DS-2DE2C200IWG-K/4G/C09S20</b>		<b>2MP 4G Sola PT Camera</b> 2MP,1920x1080,4G Connection 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Built-in mic & speaker for two-way audio Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m Built-in 8 GB eMMC storage ; IP66 for protection against dust and water Solar panel: 20 W, battery: 90 Wh 72-hour continuous power supply in proactive mode on cloudy or rainy days	<b>471</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2DE2C400IWG-K/4G/C09S20		<b>4MP,2560x1440,4G Connection</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Built-in mic & speaker for two-way audio Dual detectors – PIR + Radar combine work with higher detection accuracy , up to 12m Built-in 8 GB eMMC storage ; IP66 for protection against dust and water Solar panel: 20 W, battery: 90 Wh 72-hour continuous power supply in proactive mode on cloudy or rainy days	517
DS-2XS2T41G1-ID/4G/C05S07		<b>4MP 4G Sola Bullet Camera</b> 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux @(F1.0, AGC ON), 0 lux with LED on; 12.5fps/15fps(2560x1440, 1920x1080); 2 streams; 3D DNR; BLC; ICR; EXIR LED; Solar panel & 5VDC; Built-in 8 GB eMMC storage (6 GB available for recording); Built-in memory card slot, support microSD/SDHC/SDXC card up to 256 GB; Built-in microphone and speaker; Built-in PIR + Radar, up to 10m; Support working between 0 °C to 40 °C (32 °F to 104 °F); Hik-Connect cloud service;	388
<b>NETWORK VİDEO KAYIT CİHAZLARI</b>			
<b>4 KANAL NVR</b>			
DS-7104NI-Q1		<b>4 Kanal Q Serial mini NVR (1 SATA, H.265)</b> 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Plastic)	106
DS-7104NI-Q1/4P		<b>4 Kanal Q serial mini NVR (1 SATA, H.265, POE)</b> 40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Plastic)	179
DS-7104NI-Q1/M		<b>4 Kanal Q serial mini NVR (1 SATA, H.265)</b> 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Metal)	117
DS-7104NI-Q1/4P/M		<b>4 Kanal Q serial mini NVR (1 SATA, H.265, POE)</b> 40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Metal)	190
DS-7604NI-Q1(STD)(D)		<b>4 Kanal Q serial NVR (1 SATA, H.265)</b> 4-channels Motion Detection 2.0 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 315 1U case	172
DS-7604NI-Q1/4P(STD)(D)		<b>4 Kanal Q serial NVR (1 SATA, H.265, POE)</b> 4-channels Motion Detection 2.0 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 315 1U case	248

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>8 KANAL NVR</b>			
DS-7108NI-Q1		<b>8 Kanal Q serial mini NVR (1 SATA, H.265)</b> 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Plastic)	128
DS-7108NI-Q1/8P(D)		<b>8 Kanal Q serial mini NVR (1 SATA, H.265, POE)</b> 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Plastic)	
DS-7108NI-Q1/M		<b>8 Kanal Q serial mini NVR (1 SATA, H.265)</b> 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Metal)	135
DS-7108NI-Q1/8P/M		<b>8 Kanal Q serial mini NVR (1 SATA, H.265, POE)</b> 60Mbps Bit Rate Input Max (up to 8-ch IP video) 1 SATA interface, 8 independent PoE network interfaces, mini 1U case(Metal)	266
DS-7608NI-Q1		<b>8 Kanal Q serial NVR (1 SATA, H.265)</b> 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces,4 independent PoE network interfaces, 315 1U case	186
DS-7608NI-Q1/8P		<b>8 Kanal Q serial NVR (1 SATA, H.265, POE)</b> 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces,4 independent PoE network interfaces, 315 1U case	325
DS-7608NI-Q2		<b>8 Kanal Q serial NVR (2 SATA, H.265)</b> 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	245
DS-7608NI-Q2/8P		<b>8 Kanal Q serial NVR (2 SATA, H.265, POE)</b> 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	394
DS-7608NXI-K2		<b>8 kannel K series AcuSense NVR (2 SATA ,4K &amp; H.265)</b> All-channels Motion Detection 2.0 Facial Recognition for up to 4 channels picture stream or 1 channels video stream; * Facial recognition and Motion Detection 2.0 cannot be enabled at the same time. Support 16 face libraries, up to 20,000 face pictures in total; 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1	296
DS-7608NXI-K2/8P		<b>8 kannel K series AcuSense NVR (2 SATA 4K &amp; H.265,POE)</b> All-channels Motion Detection 2.0 Facial Recognition for up to 4 channels picture stream or 1 channels video stream; * Facial recognition and Motion Detection 2.0 cannot be enabled at the same time. Support 16 face libraries, up to 20,000 face pictures in total; 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1	496

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
<b>DS-7608NI-M2</b>		<b>8 Kanal M seral 8K NVR (2 SATA, 8K,H.265+ )</b> 8-ch 1U 8K NVR H.265+/H.265/H.264 video formats Up to 8-ch IP camera inputs Up to 8-ch@8 MP decoding capacity Up to 128 Mbps incoming bandwidth Up to 8-ch IP speakers can be connected	<b>529</b>
<b>YENİ</b>			
<b>DS-7608NI-M2/8P</b>		<b>8 Kanal M serial 8K NVR (2 SATA, 8K,H.265+ , POE)</b> 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, 8 independent PoE network interfaces, alarm I/O: 4/1, 380 1U case	<b>741</b>
<b>16 KANAL NVR</b>			
<b>DS-7616NI-Q2</b>		<b>16 Kanal Q serial NVR (2 SATA, H.265 )</b> 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	<b>270</b>
<b>DS-7616NI-Q2/16P</b>		<b>16 Kanal Q serial NVR (2 SATA, H.265,POE )</b> 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	<b>511</b>
<b>DS-7616NXI-K2</b>		<b>16 Kanal K serial Acusense NVR (2 SATA,4k&amp;H.265)</b> Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs	<b>372</b>
<b>DS-7616NXI-K2/16P</b>		<b>16 Kanal K serial Acusense NVR (2 SATA, 4K&amp;H.265, POE)</b> Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs	<b>672</b>
<b>YENİ</b>			
<b>DS-7616NI-M2</b>		<b>16 Kanal M serial 8K NVR (2 SATA, 8K &amp; H.265+ )</b> 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, alarm I/O: 4/1, 380 1U case	<b>642</b>
<b>YENİ</b>			
<b>DS-7616NI-M2/16P</b>		<b>16 Kanal M serial 8K NVR (2 SATA, 8K,H.265+ , POE)</b> 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, 8 independent PoE network interfaces, alarm I/O: 4/1, 380 1U case	<b>1011</b>
<b>32 KANAL NVR</b>			
<b>DS-7632NXI-K2</b>		<b>32 Kanal K serial Acusense NVR (2 SATA, 4K&amp;H.265)</b> Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth	<b>485</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-7732NXI-K4		<b>32 Kanal K serial Acusense NVR (4SATA, 4K&amp;H.265)</b> Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth	783
DS-7732NXI-I4		<b>32 Kanal I serial Acusense NVR (4SATA, 4K&amp;H.265+)</b> False alarm reduction for up to 4-ch 1080P; Facial Recognition for up to 4 channels picture stream or 1 channels video stream; * Facial recognition and perimeter protection cannot be enabled at the same time. Support 16 face libraries, up to 10,000 face pictures in total; 256Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces,2 HDMI outputs,1 VGA port, 1 CVBS output,1 eSATA, alarm I/O: 16/9, 1.5U case,19"	1212
<b>YENİ</b>			
DS-7732NI-M4		<b>32 Kanal M serial 8K NVR (4 SATA, 8K &amp; H.265+ )</b> 320Mbps Bit Rate Input Max(up to 32-ch IP video), 32x2MP decoding capability, 4 SATA Interfaces, 2 HDMI outputs(up to 8K),1 eSATA,alarm I/O: 16/9 1.5U case,19"	1189
<b>YENİ</b>			
DS-8632NXI-I8/S		<b>32 Kanal I serial Acusense NVR (8 SATA, Raid, H.265+)</b> 320Mbps Bit Rate Input Max(up to 32-ch IP video), 32x2MP decoding capability, 8 SATA Interfaces, 2 HDMI outputs(up to 4K),1 eSATA,alarm I/O: 16/9 2U case,19"	1843
<b>64 KANAL NVR</b>			
<b>YENİ</b>			
DS-7764NI-M4		<b>64 Kanal M serial 8K NVR (4 SATA,8K&amp;H.265+)</b> Up to 2-ch@32 MP/2-ch@24 MP/4-ch@12 MP/8-ch@8 MP/16-ch@4 MP/32-ch@1080p decoding capacity; Up to 400 Mbps incoming bandwidth and 400 Mbps outgoing bandwidth; 2 HDMI and 1 VGA interfaces, 8K or dual 4K video outputs	1406
<b>YENİ</b>			
DS-8664NXI-I8/S		<b>64 Kanal I Sereil Acusense NVR (8 SATA, Raid, H.265+)</b> 320Mbps Bit Rate Input Max(up to 64-ch IP video), 32x2MP decoding capability, 8 SATA Interfaces, 2 HDMI outputs(up to 4K),1 eSATA alarm I/O: 16/9 2U case,19"	2576
<b>DeepInmind NVR</b>			
<b>YENİ</b>			
iDS-7716NXI-M4/X		<b>16 Kanal M Sereil DeepInmind NVR (4 SATA,H 265+,,Deepleaning Feature, Large Model algorithm)</b> 256 Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, Up to 14TB per HDD,alarm I/O: 16/8, 1.5U case,19" Facial Recognition for up to 16 channels picture stream or 16 channels video stream;Support 16 face libraries, up to 100,000 face pictures per library and support 100,000 pictures in total. Video Structuralization for up to 12-ch video analysis. False alarm filtering for up to 16-ch behavior detection(line crossing, intrusion,region entrance and region exiting)	2223

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
iDS-7732NXI-M4/X		<p><b>32 Kanal M Sereil Deeplmind NVR (4 SATA,H 265+,Deepleaning Feature, Large Model algorithm)</b></p> <p>256 Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, Up to 14TB per HDD,alarm I/O: 16/8, 1.5U case,19" Facial Recognition for up to 16 channels picture stream or 16 channels video stream;Support 16 face libraries, up to 100,000 face pictures per library and support 100,000 pictures in total. Video Structuralization for up to 12-ch video analysis. False alarm filtering for up to 16-ch behavior detection(line crossing, intrusion,region entrance and region exiting)</p>	<b>2527</b>
<b>HD-TVI ÜRÜNLER (HD-TVI PRODUCTS)</b>			
<b>2MP HD TVI KAMERA 4X1</b>			
<b>YENİ</b>			
DS-2CE16D0T-EXLPF		<p><b>Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera</b></p> <p>High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging</p> <p>One port for 4 switchable signals (TVI/AHD/CVI/CVBS)</p>	<b>37</b>
<b>YENİ</b>			
DS-2CE76D0T-EXLPF		<p><b>1080p Mini IR Dome Smart Hybrid Light Kamera</b></p> <p>High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging</p> <p>One port for 4 switchable signals (TVI/AHD/CVI/CVBS)</p>	<b>37</b>
<b>YENİ</b>			
DS-2CE16D0T-LPFS (Dahili mikrofon)		<p><b>Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera</b></p> <p>High quality imaging with 2 MP, 1920×1080 resolution 2.8 mm, 3.6 mm fixed focal lens</p> <p>Up to 25 m IR distance for bright night imaging</p> <p>Up to 20 m white light distance for bright night imaging</p> <p>One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>High quality audio with audio over coaxial cable, built-in mic</p> <p>Water and dust resistant (IP67)</p> <p>Smart-Hybrid light, optimize your security with flexible lighting options</p>	<b>44</b>
<b>YENİ</b>			
DS-2CE76D0T-LPFS (Dahili mikrofon)		<p><b>1080p Mini IR Dome Smart Hybrid Light Kamera</b></p> <p>High quality imaging with 2 MP, 1920×1080 resolution 2.8 mm, 3.6 mm fixed focal lens</p> <p>Up to 20 m IR distance for bright night imaging</p> <p>Up to 20 m white light distance for bright night imaging</p> <p>High quality audio with audio over coaxial cable, built-in mic</p> <p>One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Smart-Hybrid light, optimize your security with flexible lighting options</p>	<b>44</b>
<b>YENİ</b>			
DS-2CE10DF0T-PF  ColorVu		<p><b>Harici 1080p IR Bullet Kamera (ColorVu )</b></p> <p>2M CMOS Sensor, Outdoor Bullet,0.001Lux/F1.0,0 Lux with white Light,20m,3D DNR,12 VDC,OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens,24H Color, Support TVI/AHD/CVI/CVBS video signal output</p>	<b>51</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
<b>DS-2CE10DF0T-LPFS</b> (Dahili mikrofon)		<b>Harici 1080p IR Bullet Kamera (ColorVu&amp; Smart Hybrid Light)</b> High quality imaging with 2 MP, 1920 x 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS)	<b>58</b>
<b>ColorVu</b>			
<b>YENİ</b>			
<b>DS-2CE70DF0T-LPFS</b> (Dahili mikrofon)		<b>Dahili/Harici 1080p IR Dome Kamera (ColorVu &amp; Smart Hybrid Light)</b> High quality imaging with 2 MP, 1920 x 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS)	<b>58</b>
<b>ColorVu</b>			
<b>YENİ</b>			
<b>DS-2CE12DF0T-LFS</b> (Dahili mikrofon)		<b>Dahili/Harici 1080p IR Bullet Kamera (ColorVu &amp; 40m Smart Hybrid Light)</b> 2M CMOS Sensor, Outdoor smart hybrid light Bullet, 0.001Lux/F1.0, 40m IR+40m White Light, 3D DNR, 12 VDC, Built-in Mic, Audio up Coaxial(Only TVI), OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens, 24H Color, <b>Smart Lighting (With Acusense DVR)</b> , Support TVI/AHD/CVI/CVBS video signal output	<b>78</b>
<b>ColorVu</b>			
<b>YENİ</b>			
<b>DS-2CE18D0T-LFS</b>		<b>2MP Smart Hybrid Light AOC Lamp Camera(40m IR+60m White Light+ IP67)</b> 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, Lamp looking, 40m IR+60m White Light, Outdoor Lamp Cam, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	<b>97</b>
<b>3K(5MP 16:9)) HD TVI KAMERA</b>			
<b>DS-2CE16K0T-LPFS</b> (Dahili mikrofon)		<b>Dahili/Harici 3K Hybrid Light Bullet Kamera (20mt, Metal)</b> 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), EXIR, 25m IR+20m White Light, Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	<b>62</b>
<b>DS-2CE76K0T-LPFS</b> (Dahili mikrofon)		<b>Dahili/Harici 3k Hybrid Light Dome Kamera (20mt, Plastik)</b> 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), EXIR, 20m IR+20m White Light, indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	<b>62</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
DS-2CE10KF0T-LPFS (Dahili mikrofon)  ColorVu		<b>Dahili/Harici 3k Hybrid Light Bullet Kamera</b> 3K (5MP 16:9) CMOS Sensor,3K @ 20 fps(Default),Outdoor smart hybrid light mini Bullet,0.001Lux/F1.0,20m IR+20m White Light,2D DNR,Built-in Mic,Audio up Coaxial(Only TVI),12 VDC,OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens,24H Color, Smart Lighting (With Acusense DVR) ,Support TVI/AHD/CVI/CVBS video signal output	77
<b>YENİ</b>			
DS-2CE70KF0T-LPFS (Dahili mikrofon)  ColorVu		<b>Dahili/Harici 3k Hybrid Light Dome Kamera</b> 3K (5MP 16:9) CMOS Sensor,3K @ 20 fps(Default),Indoor smart hybrid light Turret,0.001Lux/F1.0,20m IR+20m White Light,2D DNR,Built-in Mic,Audio up Coaxial(Only TVI),12 VDC,OSD Menu(Up the Coax), 2.8/3.6mm Lens,24H Color, Smart Lighting (With Acusense DVR) ,Support TVI/AHD/CVI/CVBS video signal output	77
<b>HD-TVI KAYIT CİHAZLARI (HD-TVI DVR)</b>			
<b>4 KANAL TURBO HD DVR</b>			
DS-7104HGHI-M1		<b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b> 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, mini 1U case	91
DS-7204HGHI-M1		<b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b> 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, 260 1U case	102
iDS-7104HQHI-M1/S  AcuSense		<b>4 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b> 2-ch perimeter protection , 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression,2-ch IP video input(up to 6-ch IP), 1 SATA interface Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, mini 1U case	135
<b>YENİ</b>			
DS-7104HGHI-M1/T		<b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b> Support HDTV Two-way Audio technology.full-channel motion detection 2.0 ,4 Turbo HD/AHD/Analog interface input, 4-ch HDTV coaxial video&audio input,1-ch IP video input (up to 5-ch), 1-ch RCA audio input, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case	102
<b>YENİ</b>			
DS-7204HGHI-M1/T		<b>4 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b> Support HDTV Two-way Audio technology, full-channel motion detection 2.0 ,4 Turbo HD/AHD/Analog interface input, 4-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch), 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case	113

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>  iDS-7204HQHI-M1/XT  AcuSense		<b>4 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b> <b>TVI İki Yönlü Sesi Destekleyen DVR</b> Support TVI Two-way Audio, 1-ch facial recognition or 2-ch advanced model perimeter protection , 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case	<b>157</b>
<b>YENİ</b>  iDS-7204HUHI-M1/T  AcuSense		<b>4 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP)</b> Support TVI Two-way Audio,4-ch false alarm filter,4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 4-ch IP video input(up to 8-ch IP), 1 SATA interface, H.265/H.265+ compression,Live view: 3K @20fps/ch,up to 8MP@8fps(CH1),3K @12fps/ch encoding capability, 260 1U case	<b>245</b>
<b>8 KANAL TURBO HD DVR</b>			
DS-7108HGHI-M1		<b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b> 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25(P)/30(N) fps/ch, mini 1U case	<b>113</b>
DS-7208HGHI-M1		<b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b> 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25)/(P30(N) fps/ch, 260 1U case	<b>120</b>
iDS-7108HQHI-M1/S  AcuSense		<b>8 Kanal HD-TVI Hibrit Kayıt Cihazı (5MP Lite)</b> 4-ch perimeter protection , 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 4-ch IP video input(up to 12-ch IP),1 SATA interface Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, mini 1U case	<b>219</b>
<b>YENİ</b>  DS-7108HGHI-M1/T		<b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b> Support HDTV Two-way Audio technology,full-channel motion detection 2.0 ,8 Turbo HD/AHD/Analog interface input, 8-ch HDTV coaxial video&audio input,2-ch IP video input (up to 10-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case	<b>120</b>
<b>YENİ</b>  DS-7208HGHI-M1/T		<b>8 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b> Support HDTV Two-way Audio technology,full-channel motion detection 2.0 ,8 Turbo HD/AHD/Analog interface input,8-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 10-ch), HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case	<b>131</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
iDS-7208HQHI-M1/XT 		<b>8 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b> Support TVI Two-way Audio, 2-ch facial recognition or 4-ch advanced model perimeter protection , 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case	245
<b>YENİ</b>			
iDS-7208HUHI-M1/T 		<b>8 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP)</b> Support TVI Two-way Audio,4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,8-ch HDTV1 coaxial video&audio input, 1-ch RCA audio input, 8-ch IP video input(up to 16-ch IP), 1 SATA interface, H.265/H.265+ compression, Live view: 3K @20fps/ch,up to 8MP@8fps,3K @12fps/ch encoding capability, 4K UHD output, 260 1U case	427
<b>16 KANAL TURBO HD DVR</b>			
DS-7116HGHI-M1		<b>16 Kanal HD-TVI Kayıt Cihazı (1080P lite)</b> full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input, 16-ch HDTV1 coaxial video&audio input,2-ch IP video input (up to 18-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, mini 1U case	190
DS-7216HGHI-M1		<b>16 Kanal HD-TVI Kayıt Cihazı (1080P Lite)</b> full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input,16-ch HDTV1 coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch), HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, 260 1U case	204
DS-7116HGHI-M1/T		<b>16 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b> Support HDTV1 Two-way Audio technology,full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input, 16-ch HDTV1 coaxial video&audio input,2-ch IP video input (up to 18-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case	201
DS-7216HGHI-M1/T		<b>16 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio )</b> Support HDTV1 Two-way Audio technology,full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input,16-ch HDTV1 coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch), HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case	215
<b>YENİ</b>			
iDS-7216HQHI-M1/XT 		<b>16 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b> Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, standalone 1U case	423

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
iDS-7216HUHI-M1/T 		<b>16 Kanal HD-TVI Kayıt Cihazı (8MP)</b> Support TVI Two-way Audio,4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,8-ch HDTVl coaxial video&audio input, 1-ch RCA audio input,16-ch IP video input(up to 32-ch IP), 1 SATA interface, H.265/H.265+ compression, Live view: 3K @20fps/ch,up to 8MP@8fps,3K @12fps/ch encoding capability, 4K UHD output,315 1U case	<b>872</b>
<b>32 KANAL TURBO HD DVR</b>			
DS-7232HGHI-M2		<b>32 Kanal HD-TVI Kayıt Cihazı ( 1080P Lite)</b> Deep learning based human and vehicle targets classification of Motion Detection 2.0; H.265 Pro+/H.265 Pro/H.265 video compression; HDTVl/AHD/CVI/CVBS/IP video input; Audio via coaxial cable; Up to 18-ch IP camera inputs (up to 5 MP); Up to 1080p Lite@15 fps encoding capability; Max. 1200 m for 720p HDTVl signal	<b>584</b>
<b>YENİ</b>			
iDS-7232HQHI-M2/XT 		<b>32 Kanal HD-TVI Kayıt Cihazı (5MP Lite)</b> <b>TVI İki Yönlü Sesi Destekleyin DVR</b> Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 32 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 32-ch video&1-ch audio input, 8-ch IP video input(up to 40-ch IP), H.265/H.265+ compression, 2 SATA interfaces,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, 380 1U case	<b>840</b>
<b>Monitör</b>			
<b>YENİ</b>			
DS-D5022F2-1V2(EU)		<b>21.5 inch FHD Borderless Monitor</b> 100 Hz refresh rate, more fluid and life-like video Ultra-thin device body with ultra-thin border for 3 sides. 8 bit LVDS FHD (1920 × 1080) display. Low blue light design for eye care. Multiple interfaces, including VGA, HDMI, audio out, and built-in speaker. Support VESA wall mount.	<b>220</b>
<b>YENİ</b>			
DS-D5024F2-BV2S(EU)		<b>23.8 inch FHD Borderless Monitor</b> VA technology , 178° ultra-wide view screen. 8 bit LVDS FHD (1920 × 1080) display. 100 Hz refresh rate, more fluid and life-like video. Ultra-thin device body with ultra-thin border for 3 sides. 3D noise reduction. Low blue light design for eye care. Dual interface of HDMI and VGA. Support VESA wall mount. Built-in speaker for audio input.	<b>262</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
<b>DS-D5027F2-1P2(EU)</b>		<b>27 inch FHD Borderless Monitor</b> 100 Hz refresh rate, more fluid and life-like video. IPS technology for wide, 178° ultra-wide view screen. Ultra-thin device body with ultra-thin border for 3 sides. 8 bit LVDS FHD (1920 × 1080) display. 3D noise reduction. Low blue light design for eye care. Dual interface of HDMI and VGA. Support VESA wall mount. Data Sheet	<b>350</b>
<b>YENİ</b>			
<b>DS-D5032F3-1V0S(EU)</b>		<b>31.5-inch FHD Monitor</b> 32 inch FHD 75Hz VA Monitor with Speaker VA technology, 178° ultra-wide view screen. 8 bit LVDS FHD (1920 × 1080) display. 3D noise reduction. Low blue light design for eye care. Dual interface of HDMI and VGA. Support VESA wall mount.	<b>483</b>
<b>YENİ</b>			
<b>DS-D5043F3-1V0S(EU)</b>		<b>42.5-inch FHD Monitor</b> Full HD 1920 × 1080 @60 Hz Wide viewing angle: Horizontal 178°, Vertical 178°. Ultra-thin device body with ultra-thin border for 3 sides. Multiple interfaces: HDMI, VGA, USB Build-in speaker, Audio 5W*2. Low blue light design for eye care. 3D noise reduction. Support VESA wall mount.	<b>787</b>
<b>NETWORK SWITCH</b>			
<b>DS-3E0106P-E/M (Unmanaged 100Mbps )</b>		<b>4 Port Fast Ethernet Unmanaged POE Switch</b> L2, Unmanaged, 4 10/100M RJ45 PoE ports, 4 x 10/100Mbps PoE port, and 2 x 10/100Mbps RJ45 port. IEEE 802.3at/af standard for PoE ports (Max. 35 W PoE output). IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. Wire-speed forwarding. Store-and-forward switching. Solid high-strength metal shell. Reliable fan-free design.	<b>57</b>
<b>DS-3E0310P-E/M (Unmanaged 100Mbps )</b>		<b>8 Port Fast Ethernet Unmanaged POE Switch</b> L2, Unmanaged, 8 10/100M RJ45 PoE ports 8 x 10/100 Mbps PoE port, and 2 x Gigabit RJ45 port. IEEE 802.3at/af standard for PoE ports (Max. 60 W PoE output). IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab standard. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. Wire-speed forwarding. Store-and-forward switching. Solid high-strength metal shell. Reliable fan-free design.	<b>91</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>DS-3E0318P-E/M</b> <b>(Unmanaged 100Mbps )</b>		<p><b>16 Port Fast Ethernet Unmanaged POE Switch</b> L2, Unmanaged, 16 10/100M RJ45 PoE ports Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>	<b>285</b>
<b>DS-3E0326P-E/M</b> <b>(Unmanaged 100Mbps )</b>		<p><b>24 Port Fast Ethernet Unmanaged POE Switch</b> L2, Unmanaged, 24 10/100M RJ45 PoE ports Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>	<b>357</b>
<b>YENİ</b>			
<b>DS-3E1106P-EI/M</b> <b>(Smart Managed EI 100Mbps)</b>		<p><b>4 Port Fast Ethernet Smart POE Switch</b> <b>Cloud management</b> 4 x 10/100 Mbps PoE port, 2 x 10/100 Mbps RJ45 port Total PoE Power Budget 45W Support 802.1Q VLAN Support PoE watchdog to detect and restart the cameras that do not respond Support STP/RSTP Loop prevention Support cable detection to locate failure Up to 300 m Long Range PoE Transmission 6KV Surge Protection</p>	<b>68</b>
<b>YENİ</b>			
<b>DS-3E1310P-EI/M</b> <b>(Smart Managed EI 100Mbps)</b>		<p><b>8 Port Fast Ethernet POE Switch Smart Managed</b> <b>Cloud management</b> L2, Smart Managed, 8 10/100M RJ45 PoE ports Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>	<b>110</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<p><b>YENİ</b></p> <p><b>DS-3E1318P-EI/M</b> <b>(Smart Managed EI 100Mbps)</b></p>		<p><b>16 Port Fast Ethernet POE Switch Smart Managed Cloud management</b></p> <p>L2, Smart Managed, 16 10/100M RJ45 PoE ports 16 x 10/100 Mbps PoE port, 1 x Gigabit combo, 1 x Gigabit RJ45 port. IEEE 802.3at/af standard for PoE ports. Network topology management, alarm push, network health monitor. 6 KV surge protection for PoE ports. AF/AT camera can reach up to 300 m in extend mode.</p>	293
<p><b>YENİ</b></p> <p><b>DS-3E1326P-EI/M</b> <b>(Smart Managed EI 100Mbps)</b></p>		<p><b>24 Port Fast Ethernet POE Switch Smart Managed Cloud management</b></p> <p>L2, Smart Managed, 24 10/100M RJ45 PoE ports 24 x 100 Mbps PoE RJ45 ports, 2 x gigabit combos. IEEE 802.3at/af standard for PoE ports. Network topology management, alarm push, network health monitor. 6 KV surge protection for PoE ports. AF/AT camera can reach up to 300 m in extend mode.</p>	372
<p><b>YENİ</b></p> <p><b>DS-3E1506P-EI/M</b> <b>(Smart Managed EI Gigabit)</b></p>		<p><b>4 Port Gigabit Smart POE Switch Smart Managed Cloud management</b></p> <p>L2, Smart Managed, 4 Gigabit RJ45 PoE ports 4 x Gigabit PoE port, 2 x Gigabit RJ45 port Total PoE Power Budget 60W Support 802.1Q VLAN Support PoE watchdog to detect and restart the cameras that do not respond Support STP/RSTP Loop prevention Support cable detection to locate failure Up to 300 m Long Range PoE Transmission 6KV Surge Protection</p>	76
<p><b>YENİ</b></p> <p><b>DS-3E1510P-EI/M</b> <b>(Smart Managed EI Gigabit)</b></p>		<p><b>8 Port Gigabit Smart POE Switch Smart Managed Cloud management</b></p> <p>L2, Smart Managed, 8 Gigabit RJ45 PoE ports 8 x Gigabit PoE port, 2 x Gigabit RJ45 port Total PoE Power Budget 60W Support 802.1Q VLAN Support PoE watchdog to detect and restart the cameras that do not respond Support STP/RSTP Loop prevention Support cable detection to locate failure Up to 300 m Long Range PoE Transmission 6KV Surge Protection</p>	125
<p><b>YENİ</b></p> <p><b>DS-3E1518P-EI/M</b> <b>(Smart Managed EI Gigabit)</b></p>		<p><b>16 Port Gigabit Smart POE Switch Smart Managed Cloud management</b></p> <p>L2, Smart Managed, 16 Gigabit RJ45 PoE ports 16 x gigabit PoE RJ45 ports, 1 x gigabit RJ45 port, 1 x gigabit fiber optical port Total PoE power budget 130 W Unified cloud management for security systems Network topology at your fingertips Remote troubleshooting Visualized topology management Up to 300 m long-range PoE transmission 6 kV surge protection</p>	361

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>  <b>DS-3E1526P-EI/M</b> <b>(Smart Managed EI Gigabit)</b>		<b>24 Port Gigabit Smart POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 24 Gigabit RJ45 PoE ports 24 x gigabit PoE RJ45 ports, 1 x gigabit RJ45 port, 1 x gigabit fiber optical port Total PoE power budget 230 W Unified cloud management for security systems Network topology at your fingertips Remote troubleshooting Visualized topology management Up to 300 m long-range PoE transmission	<b>502</b>
<b>YENİ</b>  <b>DS-3E1506P-EI</b> <b>(Smart Managed EI Gigabit)</b>		<b>4 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 4 Gigabit RJ45 PoE ports, 2 Gigabit RJ45 port, 802.3af/at, PoE power budget 60W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, PoE watchdog, Max. 300 meter PoE transmission, Desktop/Wall mount	<b>91</b>
<b>YENİ</b>  <b>DS-3E1510P-EI</b> <b>(Smart Managed EI Gigabit)</b>		<b>8 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 8 Gigabit RJ45 PoE ports, 2 Gigabit RJ45 port, 802.3af/at, PoE power budget 110W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, PoE watchdog, Max. 300 meter PoE transmission, Desktop/Wall mount	<b>179</b>
<b>YENİ</b>  <b>DS-3E1518P-EI</b> <b>(Smart Managed EI Gigabit)</b>		<b>16 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 16 Gigabit RJ45 PoE ports, 1 Gigabit RJ45 port, 1 Gigabit SFP port, 802.3af/at, PoE power budget 230W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, PoE watchdog, Max. 300 meter PoE transmission, Rack mount	<b>418</b>
<b>YENİ</b>  <b>DS-3E1526P-EI</b> <b>(Smart Managed EI Gigabit)</b>		<b>24 Port Gigabit High Power Smart POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 24 Gigabit RJ45 PoE ports, 1 Gigabit RJ45 port, 1 Gigabit SFP port, 802.3af/at, PoE power budget 370W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, PoE watchdog, Max. 300 meter PoE transmission, Rack mount	<b>585</b>
<b>YENİ</b>  <b>DS-3E1510P-SI</b> <b>(Smart Managed SI Gigabit)</b>		<b>8 Port Fast Ethernet POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 8 Gigabit PoE ports, 2 Gigabit SFP ports, 802.3af/at, PoE power budget 110W, max. 300 meter long distance PoE transmission, PoE watchdog, VLAN, QoS, SNMP, Port Mirroring, Storm Control, Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push and Video Control and Preview	<b>315</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>  <b>DS-3E1518P-SI</b> <b>(Smart Managed SI Gigabit)</b>		<b>16 Port Fast Ethernet POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 16 Gigabit PoE ports, 2 Gigabit SFP ports, 802.3af/at, PoE power budget 225W, max. 300 meter long distance PoE transmission, PoE watchdog, VLAN, QoS, SNMP, Port Mirroring, Storm Control, Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push and Video Control and Preview	<b>608</b>
<b>YENİ</b>  <b>DS-3E1526P-SI</b> <b>(Smart Managed SI Gigabit)</b>		<b>24 Port Fast Ethernet POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 24 Gigabit PoE ports, 2 Gigabit SFP ports, 802.3af/at, PoE power budget 370W, max. 300 meter long distance PoE transmission, PoE watchdog, VLAN, QoS, SNMP, Port Mirroring, Storm Control, Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push and Video Control and Preview	<b>760</b>
<b>YENİ</b>  <b>DS-3E1528P-SI-24P4F</b> <b>(Smart Managed SI Gigabit)</b>		<b>24 Port 4 SFP Fast Ethernet POE Switch Smart Managed Cloud management</b> L2, Smart Managed, 24 Gigabit PoE ports, 4 Gigabit SFP ports, 802.3af/at, PoE power budget 370W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, DHCP Snooping, ACL, IP&MAC filter based on port, SNMP V1/V2C, Max. 300 meter PoE transmission, Rack mount	<b>794</b>
<b>YENİ</b>  <b>DS-3T0506P</b> <b>(Industrial POE Switch)</b>		<b>4 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 4 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 120w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount	<b>524</b>
<b>YENİ</b>  <b>DS-3T0510P</b> <b>(Industrial POE Switch)</b>		<b>8 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 8 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 240w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount	<b>764</b>
<b>YENİ</b>  <b>DS-3T0306HP</b> <b>(Industrial POE Switch)</b>		<b>4 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 4 10/100M PoE ports, 1 Gigabit RJ45, 1 Gigabit SFP Uplink, 802.3af/at/bt, port 1 support Hi-PoE 60w, power budget ≤ 110w ( based on power supply, power supply unit not included ), ports 3-4 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -40~75°C, DIN rail	<b>106</b>
<b>YENİ</b>  <b>DS-3T0310HP</b> <b>(Industrial POE Switch)</b>		<b>8 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 8 10/100M PoE ports, 1 Gigabit RJ45, 1 Gigabit SFP Uplink, 802.3af/at/bt, port 1-2 support Hi-PoE 60w, power budget ≤ 110w ( based on power supply, power supply unit not included ), ports 7-8 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -40~75°C, DIN rail	<b>179</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>  <b>DS-3T0506HP</b> <b>(( Industrial POE Switch))</b>		<b>4 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 4 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 120w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount	<b>460</b>
<b>YENİ</b>  <b>DS-3T0510HP</b> <b>(Industrial POE Switch)</b>		<b>8 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 8 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at, power budget ≤ 240w ( based on power supply, power supply unit not included ), -40°C ~75°C, Din Rail Mount	<b>676</b>
<b>YENİ</b>  <b>DS-3T0506HP-E/HS</b> <b>(Industrial POE Switch)</b>		<b>4 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 4 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at/bt, port 1 support Hi-PoE 60w, PoE power budget 60W, ports 3-4 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -30~65°C, DIN rail, power supply unit is included by default, industrial power supply optional	<b>163</b>
<b>YENİ</b>  <b>DS-3T0510HP-E/HS</b> <b>(Industrial POE Switch)</b>		<b>8 Port Fast Ethernet Industrial POE Switch</b> L2, Unmanaged, 8 Gigabit RJ45 PoE ports, 2 Gigabit SFP uplink ports, 802.3af/at/bt, port 1-2 support Hi-PoE 90w, PoE power budget 110W, ports 7-8 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation, -30~65°C, DIN rail, power supply unit is included by default, industrial power supply optional	<b>281</b>
<b>DS-3E0505D-O</b>		<b>5 Port Fast Ethernet Unmanaged Desktop Switch</b> L2, Unmanaged, 5 Gigabit RJ45 ports, desktop plastic switch 5 x 10/100/1000 Mbps ethernet port Supports ADI/ADIX Store-and-forward switching Supports MAC address auto-learning and aging Simple, compact body design Supports desktop and wall-mounting Plug & play, easy to use.	<b>27</b>
<b>DS-3E0508D-O</b>		<b>8 Port Fast Ethernet Unmanaged Desktop Switch</b> L2, Unmanaged, 8 Gigabit RJ45 ports, desktop plastic switch 8 x 10/100/1000 Mbps ethernet ports Supports ADI/ADIX Store-and-forward switching Supports MAC address auto-learning and aging Simple, compact body design Supports desktop and wall-mounting Plug & play, easy to use.	<b>46</b>
<b>DS-3E0105D-O</b>		<b>5 Port Fast Ethernet Unmanaged Desktop Switch</b> L2, Unmanaged, 5 10/100M RJ45 ports, desktop plastic switch 5 x 10/100 Mbps ethernet port Supports ADI/ADIX Store-and-forward switching Supports MAC address auto-learning and aging Simple, compact body design Supports desktop and wall-mounting installation Plug & play, easy to use	<b>15</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-3E0108D-O		<p><b>8 Port Fast Ethernet Unmanaged Desktop Switch</b>            L2, Unmanaged, 8 10/100M RJ45 ports, desktop plastic switch            5 x 10/100 Mbps ethernet port            Supports ADI/ADIX            Store-and-forward switching            Supports MAC address auto-learning and aging            Simple, compact body design            Supports desktop and wall-mounting installation            Plug &amp; play, easy to use</p>	23
DS-3WF0EC-5ACT		<p><b>500m Elevator Wireless Bridge kit</b>            Elevator 5GHz wireless bridge, Max.distance 500m, 2x2 MIMO antenna with 867Mbps throughput, IEEE 802.11ac, Angle H: 50° V: 50°, 2 10/100M RJ45, 2 x 10/100 Mbps RJ45 ports, support Standard PoE input&amp;Output, DFS,TPC</p>	198
DS-3WF0EC-2NT		<p><b>200m Elevator Wireless Bridge kit</b>            Elevator 2.4GHz wireless bridge, Max.distance 500m, 2x2 MIMO antenna with 300Mbps throughput, IEEE 802.11n, Angle H: 65° V: 65°, 2 10/100M RJ45, 2 x 10/100 Mbps RJ45 ports, support 12~24V DC and passive PoE input</p>	137
DS-3WF0BC-2NT(B)		<p><b>200m Elevator Wireless Bridge kit</b>            Elevator 2.4GHz wireless bridge, Max.distance 200m, 1x1 MIMO antenna with 72Mbps throughput, IEEE 802.11n, Angle H: 50° V: 50°, 1 10/100M RJ45, support 12 VDC/1 A, support passive PoE input</p>	91
DS-3WF1000-EI-2N		<p><b>1KM Outdoor Wireless Bridge Kit</b>            Outdoor 2.4GHz wireless bridge Kit, Max.distance 1km, 2x2 MIMO antenna with 300Mbps throughput, 7dBi gain, 802.11n, Angle H: 60°, 2 100Mbps RJ45 ports, Support 12 VDC or Passive PoE Power supply, Support Web, iVMS-4200, HCP, HPP            Tested Throughput at different distance:            PTP: 70Mbps/1KM, 90Mbps/500M, 90Mbps/200M            PTMP(1 to 4): 40Mbps/1KM</p>	110
DS-3WF3000-EI-5AC/P		<p><b>3KM Outdoor Wireless Bridge Kit</b>            Outdoor 5GHz wireless bridge Kit, Max.distance 3km, 2x2 MIMO antenna with 867Mbps throughput, 8dBi gain, 802.11n, Angle H: 50°, 2 100Mbps RJ45 ports, support Standard PoE input&amp;Output, Support Web, iVMS-4200, HCP, HPP            Tested Throughput at different distance:            PTP: 40Mbps/3KM, 90Mbps/1KM, 90Mbps/500M            PTMP(1 to 4): 30Mbps/3KM</p>	175
DS-3WF02-5AC/D		<p><b>5KM Outdoor Wireless Bridge Kit</b>            Outdoor 5GHz wireless bridge CPE, Max.distance 5km, 2x2 MIMO antenna with 867Mbps throughput, 9dBi gain, output power 22dBm, 802.11a/n/ac, Angle H: 35°, 2 x 10/100 Mbps RJ45 ports, support Standard PoE input&amp;Output, HPP            Tested Throughput at different distance in PTP mode:            PTP: 40Mbps/5KM, 90Mbps/1KM, 90Mbps/500M            PTMP(1 to 4): 80Mbps/1KM</p>	220

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-3WF03C-5AC/O		<b>15KM Outdoor Wireless Bridge</b> Outdoor 5GHz wireless bridge CPE, Max.distance 15km, 2x2 MIMO antenna with 867Mbps throughput, 12dBi gain, output power 27dBm, 802.11a/n/ac, Angle H: 35°, 1 Gigabit RJ45, 1 Gigabit RJ45 with passive PoE input, TDMA, DFS, TPC, Smart Managed	156
DS-3WF0FC-2N/O		<b>1KM Outdoor Wireless Bridge</b> Outdoor 2.4GHz wireless bridge CPE, Max.distance 1km, 2x2 MIMO antenna with 300Mbps throughput, 7dBi gain, 802.11n, Angle H: 35°, 2 100Mbps RJ45 ports, Support 12 VDC or Passive PoE Power supply, Support Web, iVMS-4200, HCP Point to point: Support up to 4-ch IPC (2MP) in Max. 1 KM distance and Max. 20 Mbps bandwidth Point to multi-point: Support up to 4-ch IPC (2MP) in Max. 1 KM distance and Max. 20 Mbps bandwidth within 35° ± 5°, Max. 1 to 4 PTMP connection	68
DS-3WF3000S-EI-5AC/P		<b>3KM Outdoor Wireless Bridge</b> Outdoor 5GHz wireless bridge CPE, Max.distance 3km, 2x2 MIMO antenna with 867Mbps throughput 8dBi gain, output power 22dBm, 802.11a/n/ac, Angle H: 50°, 2 × 10/100 Mbps RJ45 ports, support Standard PoE output	376
DS-3WF02C-5AC/O		<b>5KM Outdoor Wireless Bridge</b> Outdoor 5GHz wireless bridge CPE, Max.distance 5km, 2x2 MIMO antenna with 867Mbps throughput, 9dBi gain, output power 22dBm, 802.11a/n/ac, Angle H: 35°, 1 Gigabit RJ45, 1 Gigabit RJ45 with passive PoE input, TDMA, DFS, TPC, Smart Managed	114
DS-3WAP522-SI		<b>Wi-Fi 5 1200M In-Wall Access Point</b> 1200 Mbps Dual-band Wi-Fi 5 Gigabit ceiling mount indoor AP, 2x2 MIMO, 1 Gigabit port with PoE in, Max/Recommend user access is 256/80, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)	152
DS-3WAP622G-SI		<b>Wi-Fi 6 1800M Ceiling Access Point</b> 1800 Mbps Dual-band Wi-Fi 6 Gigabit ceiling mount indoor AP, 2x2 MIMO, 1 Gigabit port with PoE in, Max/Recommend user access is 256/100, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)	232
DS-3WAP622E-SI		<b>Wi-Fi 6 3000M Ceiling Access Point</b> 3000 Mbps Dual-band Wi-Fi 6 Gigabit ceiling mount indoor AP, 2x2 MIMO, 1 2.5G Multi-Giga port with PoE in, Max/Recommend user access is 256/100, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)	285

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-3WAP521-SI		<b>Wi-Fi 5 1200M In-Wall Access Point</b> 1200 Mbps Dual-band Wi-Fi 5 Gigabit in-Wall indoor AP, 2x2 MIMO, 2 Gigabit port with 1 PoE in, Max/Recommend user access is 128/50, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, 86 mm standard wall junction box	152
DS-3WAP621E-SI		<b>Wi-Fi 6 3000M In-Wall Access Point</b> 3000 Mbps Dual-band Wi-Fi 6 Gigabit in-Wall indoor AP, 2x2 MIMO, 2 Gigabit port with 1 PoE in, Max/Recommend user access is 256/70, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, 86 mm standard wall junction box	285
DS-3WAP623E-SI		<b>Wi-Fi 6 3000M Outdoor Access Point</b> 3000 Mbps Dual-band Wi-Fi 6 Gigabit outdoor AP, 2x2 MIMO, 1 Gigabit port with PoE in, IP68, Max/Recommend user access is 256/100, HPP/HC unified cloud app management, Support batch managed via AC Router, Support standalone configuration via AP's web, DC 12V(Note: power adapter is not included, suggest using POE for power supply, no need additional power adapter)	361
DS-3WG105G-SI		<b>All in One 5 Port AC Router</b> Concurrent Users 100, Up to 2 WAN Loadbalancing, 1 Gigabit WAN Port, 4 Gigabit PoE LAN Ports with 1 LAN/WAN Switchable, 32 APs, 58w, IPSec throughput 100Mbps, 40K Concurrent sessions, Desktop/Wall	167
DS-3WG105GP-SI		<b>All in One 5 Port PoE AC Router</b> Concurrent Users 100, Up to 2 WAN Loadbalancing, 1 Gigabit WAN Port, 4 Gigabit PoE LAN Ports with 1 LAN/WAN Switchable, 32 APs, 58w, IPSec throughput 100Mbps, 40K Concurrent sessions, Desktop/Wall	201
DS-3WG210GP-SI		<b>All in One 10 Port PoE AC Router</b> Concurrent Users 200, Up to 4 WAN Loadbalancing, 2 Gigabit WAN Ports with 1 WAN/LAN Switchable, 8 Gigabit PoE LAN Ports with 2 LAN/WAN Switchable, 200 APs, 75w, IPSec throughput 100Mbps, 40K Concurrent sessions, Desktop	304
<b>Kablo (Network Cable)</b>			
DS-1LN6UZC0 <b>(Solid Copper)</b>		<b>Network Kabloları CAT 6</b> 305 m CAT6 UTP Network Cable Stable electrical performance, compliant with ANSI/TIA-568.2-D, IEC61156, ISO/IEC11801. Compliant with RoHS 2.0. • Sheath with strong mechanical properties, and high tensile and compressive strength, reducing damage during the project. • Excellent performance in the Fluke 90-meter permanent link test while working continuously at 50°C high temperature. • Excellent performance in the Fluke 100-meter channel test while being continuously loaded with 57V/1A DC power (PoE). • Solid-Bare Copper conductor with less resistance, and better electrical properties and transmission performance.	281

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<b>YENİ</b>			
<b>DS-1LN6U-W/CCA (CCA)</b>		<b>Network Kabloları CAT 6</b> 305 m CAT6 UTP Network Cable (CCA,0.565 mm) 305 m cost-effective CAT6 CCA network cable Full diameter and full length Quality verified by Fluke test Guaranteed long PoE transmission distance	<b>160</b>
<b>DS-1LN6U-G (Solid Copper)</b>		<b>Network Kabloları CAT 6</b> 305 m CAT6 UTP Network Cable (Solid Copper, 0.55 mm, Gray) Full diameter 305 m CAT6 network cable Core diameter: 0.55mm Excellent transmission performance using solid copper Quality verified by Fluke test Guaranteed long PoE transmission distance Great PVC flame resistance.	<b>334</b>
<b>YENİ</b>			
<b>DS-1LN6OUSPE (Solid Copper-Outdoor)</b>		<b>Network Kabloları CAT 6</b> DS-1LN6OUSPE CAT6 U/UTP Outdoor Network Cable (Solid Copper, 0.55mm) Stable electrical performance, compliant with ANSI/TIA-568.2-D, IEC61156, ISO/IEC11801. Compliant with RoHS 2.0. Sheath with strong mechanical properties, and high tensile and compressive strength, reducing damage during the project. Excellent performance in the Fluke 90-meter permanent link test while working continuously at 50°C high temperature. Excellent performance in the Fluke 100-meter channel test while being continuously loaded with 57 V/1 A DC power (PoE). Solid-Bare Copper conductor with less resistance, and better electrical properties and transmission performance.	<b>376</b>
<b>DS-1LN6-UU (Solid Copper-)</b>		<b>Network Kabloları CAT 6</b> 305 m CAT6 UTP Network Cable (Solid Copper, 0.565 mm, CM) Full diameter 305 m CAT6 network cable Core diameter: 0.565mm Excellent transmission performance using solid copper Quality verified by Fluke test Guaranteed long PoE transmission distance Great PVC flame resistance.	<b>376</b>
<b>Kontrol Klavyesi (Key board)</b>			
<b>DS-1100KI</b>		<b>Network Kontrol Klavyesi</b> Divide video wall into regions to manage video wall by region open/close window, move window, resize window, divide window, and enlarge/narrow sub-window. Group and macro Preview camera live image on network keyboard touchscreen Quickly switch to the previous/next camera Control speed dome movement via joystick Play the decoder videos on video wall Play the video recorder videos on network keyboard touchscreen. Supports clipping and capturing during playback Add devices via SDK or ONVIF protocol HikCentral and KPS platforms access Support up to 32 users (1 administrator and 31 operators) and 4,000 devices;Add/modify/delete cameras in batch Import/export configuration file	<b>1862</b>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-1200KI		<b>Network Kontrol Klavyesi</b> Full-featured network keyboard Supports various cameras, NVRs, DVRs Flexible 4-axis joystick Buttons can be used to perform powerful functions 128 x 64 screen displays all important information	627
DS-1005KI		<b>USB Kontrol Klavyesi</b> Full-featured USB keyboard Supports various cameras, NVRs, DVRs and also iVMS 4200 Flexible 4-axis joystick Buttons can be used to perform powerful functions	399
<b>UPS</b>			
<b>YENİ</b>			
DS-UPS600(O-STD)/EU		<b>600VA/360W UPS</b> 600VA/360W,220V Backup UPS with universal port sockets and European plug Socket Number 2 Battery Capacity 12V/7Ah Battery Number 1	103
<b>YENİ</b>			
DS-UPS1000(O-STD)/EU		<b>1000VA/600W UPS</b> 1000VA/600W,220V Backup UPS with universal port sockets and European plug Socket Number 2 Battery Capacity 12V/9Ah Battery Number 1	129
<b>YENİ</b>			
DS-UPS2000(O-STD)/EU		<b>2000VA/1200W UPS</b> 2000VA/1200W,220V Backup UPS with universal port sockets and European plug Socket Number 4 Battery Capacity 12V/9Ah Battery Number 2	365
<b>YENİ</b>			
DS-UPS3000(O-STD)/EU		<b>3000VA/1800W UPS</b> 3000VA/1800W,220V Backup UPS with universal port sockets and European plug Socket Number 4 Battery Capacity 12V/9Ah Battery Number 4	528

## FİYAT LİSTESİ KULLANIM ŞARTLARI

- Bu liste fiyatı üretici tarafından önerilen fiyat listesidir.
- Ürünlerimiz 2 yıl ithalatçı firma garantisindedir.
- Vergi oranlarındaki değişiklikler fiyatlarımıza aynen yansıtılır.
- Belirtilen fiyatlara KDV oranı dahil değildir.
- Kayıt cihazlarında harddisk yoktur.Box Kameralara Lens dahil değildir.
- Fiyat listesinde belirtilen, fiyat bilgileri ,ürün kodları, ürün özellikleri, ürün açıklamaları değişiklik gösterebilir.
- Stoklar ve bulunmayan ürünlerin teslim süresi için Yetkili Distribütör firmadan bilgi alınması rica olunur.
- HIKVISION Dijital Teknoloji önceden haber vermeksizin listede yer alan fiyat koşullarını değiştirme haklarını gizli tutar.
- Oluşabilecek yazım, baskı ve dizgi hataları bağlayıcı değildir.